



控制箱 配線箱



金屬控制/配線箱

產品特色

- 全焊式焊接 · 德國PU無縫墊圈 · 120度工業用強化後鈕
- 防水防塵IEC 60529 IP66 & 防撞擊IEC 62262 IK10
- RAL 7035粉體塗裝 · 使用於室外美觀耐用
- 箱體底部預留下封板 · 方便電線電纜導入
- 門板可左右互換 · 可依需求調整
- 提供客製化開孔加工等服務

品號	尺寸 (寬x高x深)	衝擊防護 等級	IP 等級	出線孔	鎖頭 數量
FT 202015	200x200x150mm	IK10	66	ax1	1
FT 302015	300x200x150mm	IK10	66	ax1	1
FT 302515	300x250x150mm	IK10	66	ax1	1
FT 302520	300x250x200mm	IK10	66	ax1	1
FT 303015	300x300x150mm	IK10	66	bx1	1
FT 303020	300x300x200mm	IK10	66	bx1	1
FT 304015	300x400x150mm	IK10	66	ax2	1
FT 304020	300x400x200mm	IK10	66	cx1	1
FT 403015	400x300x150mm	IK10	66	bx1	1
FT 403020	400x300x200mm	IK10	66	bx1	1
FT 404020	400x400x200mm	IK10	66	ax1	1
FT 404030	400x400x300mm	IK10	66	ax1	1
FT 406020	400x600x200mm	IK10	66	bx1	1
FT 406030	400x600x300mm	IK10	66	bx1	1
FT 503020	500x300x200mm	IK10	66	ax2	2
FT 504020	500x400x200mm	IK10	66	cx1	2
FT 504025	500x400x250mm	IK10	66	cx1	2
FT 505020	500x500x200mm	IK10	66	cx1	2
FT 505025	500x500x250mm	IK10	66	cx1	2

控制箱
·
配線箱

品號	尺寸 (寬x高x深)	衝擊防護等級	IP 等級	出線孔	鎖頭 數量
FT 604020	600x400x200mm	IK10	66	cx1	2
FT 604030	600x400x300mm	IK10	66	cx1	2
FT 605025	600x500x250mm	IK10	66	cx1	2
FT 606020	600x600x200mm	IK10	66	dx1	2
FT 606025	600x600x250mm	IK10	66	dx1	2
FT 606030	600x600x300mm	IK10	66	dx1	2
FT 606040	600x600x400mm	IK10	66	dx1	2
FT 705020	700x500x200mm	IK10	66	cx1	2
FT 705025	700x500x250mm	IK10	66	cx1	2
FT 806020	800x600x200mm	IK10	66	dx1	2
FT 806030	800x600x300mm	IK10	66	dx1	2
FT 806040	800x600x400mm	IK10	66	dx1	2
FT 808025	800x600x250mm	IK10	66	cx2	2
FT 808030	800x800x300mm	IK10	66	cx2	2
FT 1006025	1000x600x250mm	IK10	66	dx1	3
FT 1006030	1000x600x300mm	IK10	66	dx1	3
FT 1006040	1000x600x400mm	IK10	66	dx1	3
FT 1008025	1000x800x250mm	IK10	66	cx2	3
FT 1008030	1000x800x300mm	IK10	66	cx2	3
FT 1206030	1200x600x300mm	IK10	66	dx1	3
FT 1206040	1200x600x400mm	IK10	66	dx1	2